

THE FLOORING GUYS

PRODUCT SPECIFICATIONS

Type	Hybrid	Style	Single Plank LVT
Description	Stone Polymere Core deaturing Licensed Click System		
Board Construction	0.5mm wear layer and 4.5mm core		
Installation Method	Floating	Finish	Textured Matt Finish
Coating	Gloss leve 5 - 8%	Profile	Micro-bevel edge on four sides
Dimensions	1535 x 226 x 6.5mm	Boards per Pack	6
m² per Pack	2.082m ²	m² per Pallet	108.26m ²
Pack Weight	23.5kg	Colours	10 Decors
Underlay	1.5mm high density closed cell foam attached		

TEST DATA

Slip Resistance	P3	Underfloor Heating	Suitable to a maximum of 27°C
Load Test	0.02mm at 250 PSI	Emissions Test	No Disclosed Formaldehyde (EO)
Castor Chair Suitability	Heavy Commercial	Fire Test	Critical Heat Flux: 5.8kW/m ²
Acoustic Test	LnTw 55	Underfloor Heating	Suitable to a maximum of 27°C
		Floor Score Certification	Floor Score Certified

Warranty	25 Year Residential Warranty 10 Year Commercial Warranty
Moisture resistance	Lifetime waterproof warranty

PRODUCT COLOURS

