



# Olympus



100  
**Parchment**



180  
**Fumed Oak**



300  
**Autumn Oak**



350  
**Chestnut**



540  
**River Oak**



545  
**Blackbutt**



550  
**Western  
Tallowood**



555  
**Spotted Gum**



655  
**Forest Reds**



710  
**Frosted Oak**



720  
**Summit Oak**



750  
**Carbonised  
Oak**

\*Subject to proper installation and maintenance. While all care is taken, product images may vary in colour due to possible printing process variations. Images are to be used as a guide only to give an idea of the colour and nuances of the pattern, but are not fully representative of the variations among the planks (which reflects the natural product which inspired the design). For a representative view of the surface structure and variations within the design, take a look at the big samples on display and ask your retailer for more advice.

# Olympus



Combining durability, water resistance<sup>^</sup> and easy maintenance, the Olympus DS vinyl plank range is the perfect choice for home owners wanting a beautiful timber look that is suitable for all areas of the home. Godfrey Hirst vinyl plank is quiet underfoot, with a durable wear layer to provide protection against everyday wear and tear, making Olympus DS ideal for busy family homes.

## Technical Data

Type	Vinyl Plank	M <sup>2</sup> per Box	3.14m <sup>2</sup>
Plank Thickness	2.5mm	M <sup>2</sup> per Pallet	219.8m <sup>2</sup>
Wear Layer	0.5mm	Finish	Matte
Dimensions	1219mm (L) x 184mm (W)	Surface	Embossed
Planks per Box	14	Profile	Micro Bevel
Colours	12	Protective Coating	PUR + Scratch Resist + Stain Resist
Installation Method	Direct Stick Plus		

## Performance

Classification	23, 33	ISO 10582
Dimensional Stability	Length: 0.05% Width: 0.00% Curling: 0.00%	ISO 23999
Abrasion Rating	Group T	EN 660-2
Residual Indentation	0.03mm	ISO 24343-1
Castor Chair	No Damage	ISO 4918
Impact Sound Reduction	<b>Test Application</b> 150mm Slab + 28mm Furrings + 10mm Plasterboard 200m Slab 200mm Slab + 28mm Furrings + 10mm Plasterboard 200mm Slab + R2.5 Insulation + 100mm Cavity + 10mm Plasterboard 250mm Slab + 28mm Furrings + 10mm Plasterboard	<b>Ln'T,w Result</b> <b>No underlay</b> 66 70 65 62 64  <b>Ln'T,w Result</b> <b>Underlay: 2mm rubber</b> 54 58 53 50 52  ISO140-7 / ISO717.2
Light Fastness	≥ 6	EN ISO 105-B02
Light Reflectiveness Values	100 Parchment 40.98% 350 Chestnut 28.92% 550 Western Tallowood 24.81% 710 Frosted Oak 36.55%	180 Fumed Oak 9.38% 540 River Oak 18.27% 555 Spotted Gum 18.5% 720 Summit Oak 24.79%
Fire Classification	10.7 kW/m <sup>2</sup> Smoke Value 53%.min	EN ISO 9239
Slip Resistance	P2	AS 4586
Suitable for wet areas	Yes - subject to proper installation and maintenance	
Recommended Adhesive	Refer to Godfrey Hirst Adhesive Guide <a href="http://www.godfreyhirst.com">www.godfreyhirst.com</a>	
Residential Warranty*	25 Year Vinyl Plank Limited Residential Warranty	
Commercial Warranty†	15 Year Commercial Warranty available upon request	

## Sustainability

VOC Rating	Passes CETEC VOC test
Accreditation	Manufactured under a management system certified as complying with ISO 9001 & ISO14001



Manufactured under a quality and environmental system certified as complying with ISO9001 and 14001. Test results and certificates are available on request. Specifications and colourations are subject to manufacturing tolerances. As part of Godfrey Hirst's continuous improvement process, Godfrey Hirst reserves the right to change the specifications of or delete colours of this product without notice. All Godfrey Hirst vinyl plank floors must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Vinyl Plank Floors Installation Instructions. \*These residential warranties are in addition to consumers' rights under the statutory consumer guarantee provisions in the Australian Consumer Law, which may exceed the rights under these warranties. Conditions apply: Warranties apply to residential indoor use of the floor installed and maintained in accordance with Godfrey Hirst's guidelines. The amount recoverable under the warranties decreases after five years. For full information in respect to the scope and limitations of these warranties, refer to the Godfrey Hirst Vinyl Plank Floors Care, Maintenance and Warranties guide (which also includes full information as to the installation, care and characteristics of Godfrey Hirst vinyl plank products) available from your retailer, by calling 1300 444 778, or by download from [www.godfreyhirst.com](http://www.godfreyhirst.com). †Terms and conditions apply to all commercial warranties – contact your Godfrey Hirst account manager.